Issuing date 23-Apr-2015

Revision Date 23-Apr-2015

Version 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier
Product name
Product number

TEX COAT CHIPGUARD BLACK 4313

<u>Product Type</u> Synonyms <u>Supplier's details</u>	Extremely flammable aerosol None	
Recommended Use Uses advised against	Chip Guard. For Professional and Industrial Use Only. Not for sale to the general public.	
Manufacturer/Supplier:	Transtar Autobody Technologies 2040 Heiserman Drive Brighton, MI 48116 810-360-1600	
Emergency telephone number Chemical Emergency Phone Number	CHEMTREC: +001-703-527-3887 (INTERNATIONAL) 1-800-424-9300 (NORTH AMERICA)	

## 2. HAZARDS IDENTIFICATION

## Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation Category 2A	
Carcinogenicity	Category 2
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

### GHS Label elements, including precautionary statements

# **Emergency Overview** DANGER Hazard Statements Causes skin irritation Causes serious eye irritation Suspected of causing cancer May damage fertility or the unborn child May cause drowsiness or dizziness May cause damage to organs (central nervous system, eyes, kidney, liver, respiratory system, and skin) through prolonged or repeated exposure. May be fatal if swallowed and enters airways Extremely flammable aerosol Contains gas under pressure; may explode if heated Physical state Aerosol **Odor** Solvent Appearance opaque

## **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

## **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep container tightly closed Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

## Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

None

## Other information

Toxic to aquatic life with long lasting effects

5.06E-06% of the mixture consists of ingredient(s) of unknown toxicity

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
DIMETHYLETHER	115-10-6	20-30
2-BUTANONE	78-93-3	10-20
TOLUENE	108-88-3	10-20
CALCIUM CARBONATE	1317-65-3	10-20
BUTYL BENZYL PHTHALATE	85-68-7	1-10
BUTYL ACETATE	123-86-4	1-10
CARBON BLACK	1333-86-4	0.1-1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

## First aid measures for different exposure routes

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

## 4313

### Most important symptoms/effects, acute and delayed

Main SymptomsCauses skin and eye irritation. Irritating to respiratory system. May cause drowsiness or<br/>dizziness. May damage to fertility or the unborn child. May cause cancer. Harmful or fatal<br/>if swallowed and enters airways. Causes damage to organs through prolonged or repeated<br/>exposure.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Treat symptomatically.

## **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Water fog.Dry chemical. Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Cool containers / tanks with water spray. Keep away from sources of ignition - No smoking.

#### Specific hazards arising from the chemical

Extremely flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

#### Explosion Data Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge none.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans.Do no stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat,flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.			
Environmental precautions				
Environmental precautions	Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.			
Methods and materials for containment and cleaning up				
Methods for Containment	Prevent further leakage or spillage if safe to do so. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.			
Methods for cleaning up	Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take precautionary measures against static discharges.			

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling	Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges.
Conditions for safe storage, inclue	ding any incompatibilities
Technical measures/Storage conditions	Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.
Incompatible products	None known based on information supplied.
Aerosol Level	2

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-BUTANONE 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m <sup>3</sup> (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m <sup>3</sup>	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
CALCIUM CARBONATE 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
BUTYL ACETATE 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
CARBON BLACK 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	(vacated) TWA: 3.5 mg/m³	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

ACGIH: (American Conference of Governmental Industrial Hygienists) OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines** 

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls** 

**Engineering Measures** 

Showers Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Safety glasses with side-shields.		
Skin and body protection	Chemical resistant apron. Protective gloves.		
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.		
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice.		
9. PHYSICAL AND CHEMICAL PROPERTIES			

#### **Physical and chemical properties**

Physical state Appearance Color	Aerosol opaque black	Odor Odor Threshold	Solvent No information available
Property	<u>Values</u>	Remarks • Methods	
pH Malting/freezing point	No information available No information available		
Melting/freezing point	No information available		
Boiling point/boiling range Flash Point	-41.1 °C / -42 °F	Based on propellant	
Evaporation rate	No information available	Dased on propenant	
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit	No information available		
lower flammability limit	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific Gravity	.948		
Water solubility	Practically insoluble		
Partition coefficient: n-octanol/wate	erNo information available		
Autoignition temperature	No information available		
Decomposition temperature	No information available		
Viscosity	No information available		
Explosive properties	No information available		
Other information			
VOC Content(%)	72.13		

## **10. STABILITY AND REACTIVITY**

## Reactivity

No data available

#### <u>Chemical stability</u> Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

#### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

### **Incompatible Materials**

None known based on information supplied.

### **Hazardous Decomposition Products**

None known based on information supplied.

## **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Inhalation	Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.
Eye contact	Irritating to eyes. Avoid contact with eyes.
Skin contact	Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin.
Ingestion	May be harmful if swallowed. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

#### **Component Information**

**Product Information** 

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIMETHYLETHER 115-10-6	-	-	= 308.5 mg/L (Rat)4 h
2-BUTANONE 78-93-3	= 2483 mg/kg(Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat)4 h
TOLUENE 108-88-3	= 2600 mg/kg(Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat)4 h
BUTYL BENZYL PHTHALATE 85-68-7	= 2330 mg/kg (Rat)	= 6700 mg/kg (Rat)	> 6.7 mg/L (Rat)4 h
BUTYL ACETATE 123-86-4	= 14000 mg/kg(Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat)4 h

#### Information on toxicological effects

**Symptoms** 

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to respiratory system. Causes serious eye irritation.Irritating to skin. May be harmful or fatal if ingested.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Eye damage/irritation	Irritating to skin. Irritating to eyes.
Irritation	Irritating to eyes, respiratory system and skin.
Sensitization	None known.
Germ Cell Mutagenicity	None known.
Carcinogenicity	The table below indicates whether each agency has evaluated a listed ingredient as a
	carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE	-	Group 3	-	-
108-88-3				
BUTYL BENZYL PHTHALATE 85-68-7	-	Group 3	-	-
CARBON BLACK 1333-86-4	A3	Group 2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans

**Reproductive toxicity** 

Product is or contains a chemical which is a known or suspected reproductive hazard.

Specific target organ systemic toxicity (single exposure)	May cause drowsiness and dizziness. May cause respiratory irritation.
Specific target organ systemic toxicity (repeated exposure)	May cause damage to organs through prolonged or repeated exposure.
Chronic toxicity	May cause adverse liver effects.
Target Organ Effects	Central nervous system, Eyes, Kidney, Liver, Respiratory system, Skin.
Neurological effects	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Aspiration hazard	May be fatal if swallowed and enters airways.

## Numerical measures of toxicity - Product Information

Unknown Acute Toxicity	5.06E-06% of the mixture consists of ingredient(s) of unknown toxicity
The following values are calculated	d based on chapter 3.1 of the GHS document .
ATEmix (oral)	48960 mg/kg
ATEmix (dermal)	13112 mg/kg
ATEmix (inhalation-dust/mist)	146.9 mg/l
ATEmix (inhalation-vapor)	33475 mg/l

# **12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
2-BUTANONE 78-93-3	-	3130 - 3320 mg/L LC50 Pimephales promelas 96h flow-through	-	4025 - 6440 mg/L EC50 Daphnia magna 48h Static 5091 mg/L EC50 Daphnia magna 48h 520 mg/L EC50 Daphnia magna 48h
TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static 12.6 mg/L LC50 Pimephales promelas 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 54 mg/L LC50 Oryzias latipes 96h static	-	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h
BUTYL BENZYL PHTHALATE 85-68-7	0.02 - 0.25 mg/L EC50 Pseudokirchneriella subcapitata 96h 0.2 - 28.2 mg/L EC50 Pseudokirchneriella subcapitata 72h	1.0 - 10.0 mg/L LC50 Lepomis macrochirus 96h static 1.0 - 10.0 mg/L LC50 Oncorhynchus mykiss 96h static 1.39 - 3.88 mg/L LC50 Pimephales promelas 96h flow-through 0.82 mg/L LC50 Oncorhynchus mykiss 96h flow-through 0.78 mg/L LC50 Pimephales promelas 96h static		0.9 - 1.1 mg/L EC50 Daphnia magna 48h Static 0.97 mg/L EC50 Daphnia magna 48h 1.28 mg/L EC50 Daphnia magna 48h semi-static 0.76 mg/L EC50 Daphnia magna 48h Flow through
BUTYL ACETATE 123-86-4	674.7 mg/L EC50 Desmodesmus subspicatus 72h	17 - 19 mg/L LC50 Pimephales promelas 96h flow-through 100 mg/L LC50 Lepomis macrochirus 96h static	-	-

## Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

Chemical Name	log Pow
DIMETHYLETHER	-0.18
115-10-6	
2-BUTANONE	0.29
78-93-3	
TOLUENE	2.65
108-88-3	
BUTYL BENZYL PHTHALATE	4.91
85-68-7	
BUTYL ACETATE	1.81
123-86-4	

Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

Waste treatment	
Waste Disposal Methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated packaging	Do not re-use empty containers.

## **14. TRANSPORT INFORMATION**

DOT Ground CONSUMER COMMODITY ORM-D or LIMITED QUANTITY

ΙΑΤΑ	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.
IMDG	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

## **15. REGULATORY INFORMATION**

## International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
DIMETHYLETHER	Х	X	Х	Х	Х	Х	Х	Х
2-BUTANONE	Х	X	Х	Х	Х	Х	Х	Х
TOLUENE	Х	X	Х	Х	Х	Х	Х	Х
CALCIUM CARBONATE	Х	Х	Х	Х	Х	Х	Х	Х
BUTYL BENZYL PHTHALATE	Х	X	X	Х	Х	Х	Х	Х

BUTYL ACETATE	Х	Х	Х	Х	Х	Х	Х	Х
CARBON BLACK	Х	Х	Х	Х	Х	Х	Х	Х

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	10-20	1.0
SARA 311/312 Hazard Categories			
Acute Health Hazard	Yes		
Chronic Health Hazard	Yes		
Fire Hazard	Yes		
Sudden Release of Pressure Hazard	Yes		
Reactive Hazard	no		

#### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	Х	Х
BUTYL BENZYL PHTHALATE 85-68-7		X	Х	
BUTYL ACETATE 123-86-4	5000 lb			Х

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
2-BUTANONE 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
BUTYL BENZYL PHTHALATE 85-68-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
BUTYL ACETATE 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

## U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65	
TOLUENE - 108-88-3	Developmental	
	Female Reproductive	
BUTYL BENZYL PHTHALATE - 85-68-7	Developmental	
CARBON BLACK - 1333-86-4	Carcinogen	

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
DIMETHYLETHER 115-10-6	Х	X	Х
2-BUTANONE 78-93-3	Х	Х	Х
TOLUENE 108-88-3	Х	Х	Х
CALCIUM CARBONATE 1317-65-3	Х	X	Х
BUTYL BENZYL PHTHALATE 85-68-7	Х	X	Х
BUTYL ACETATE 123-86-4	Х	Х	Х
CARBON BLACK 1333-86-4	Х	X	Х

EPA Pesticide Registration Number Not applicable

#### <u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION					
<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards	
<u>HMIS</u>	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B	
Prepared By	Transtar Autobody Technologies				

Issuing date	23-Apr-2015
Revision Date	23-Apr-2015
Revision Note	
No information available	
Disalaiman	

**Disclaimer** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

#### End of Safety Data Sheet